## **Material Safety Data Sheet**



## 30% CALCIUM PEROXIDE

**Product: CALCIUM PEROXIDE** 

Manufacturer: Siam Aqua Tech Development System Co., Ltd.

Emergency Telephone Nos.: 66-83-1454522 (24 Hours)

66-2-0067571 (Office Hours)

Product Information		
Synonyms	Calcium Peroxide	
Formula	CaO <sub>2</sub> (CAS. No. 1305-79-9)	
Product Uses	It is a versatile chemical and is used extensively as	
	an oxidizing agent for food, environmental, cosmetics,	
	starch modification, fisheries, aquacultures and other	
	applications.	
Additional	At room temperature, calcium peroxide is an	
Information	extremely stable compound. The stability is affected if	
	kept in elevated temperatures in humid atmosphere,	
	or when wet.	
Precautionary Information		
Health	Airborne dust is irritating to eyes, nose, throat and	
	lungs. No significant long term inhalation hazard;	
	irritation subsides after exposure ceases.	
Physical	Reacts with moisture to liberate oxygen which	
	initiates or promotes combustion in other materials.	

	<u> </u>		
	Decomposes to	o release oxygen at elevated	
	temperatures.		
Ingredients			
Calcium Peroxide (CaO <sub>2</sub> ), (CAS.		30%	
No. 1305-79-9)			
Calcium hydroxide (Ca(OH) <sub>2</sub> ),		50%	
(CAS. No. 1305-62-0)			
Other calcium salts		20%	
Physical Data			
Melting Point	Decomposes o	n heating	
Appearance and	Cream colored powder		
state			
Odor	Odorless		
Specific Gravity	Approx. 2.92		
	[Bulk density=2	27 Lbs/Cu.ft or 12 Kg/ 0.028317 Cu.m	
	or <u>423.77 Kg/1</u>	Cu.m]	
Solubility in water	Insoluble		
pH (1% slurry)	12-13		
Hazard Class	Oxidizer		
Fire, Explosion and Reactivity Data			
Flash Point	Not applicable		
Auto ignition	Not applicable		
Temperature			
Extinguishing	Water		
media			

Special Fire	Full protective clothing. Consider calcium peroxide as	
Fighting	a strong oxidizer. Cool exposed containers with	
Procedures	water.	
Degree of Fire	Non combustible, decomposes with liberation of	
and Explosion	oxygen.	
Hazard		
Conditions to	Excessive heat, moisture and grinding mixtures with	
avoid	organics	
Major	Heat, moisture, Reducing agents	
Contaminants		
that contribute to		
instability		
Incompatibility	With heavy metal	
Routes of Exposure		
Eye Contact	Severely irritating to unwashed eyes; minimally	
	irritating to washed eyes (rabbit)	
Skin Contact	Non irritating (rabbit)	
Skin Absorption	No significant hazard (rabbit)	
Inhalation	1 Hr LC50 above 17 mg/L (rat)	
Ingestion	No significant hazard	
	Oral LD 50 above 5 gms/kg (rat)	
Effects of Over Exposure		
Acute Exposure	Dust irritating to eyes, nose, throat and lungs	
	Emergency and First Aid Procedures	

Eyes	Immediately flush with large amount of water for at	
	least 15 minutes. Check immediately with eye	
	specialist.	
Skin	Wash with large amount of water. If irritation persists,	
	obtain medical attention	
Inhalation	Remove to fresh air. Call a doctor.	
Ingestion	If swallowed, drink plenty of water. See a doctor.	
Decontamination	Wash with soap and water.	
Procedure		
Notes to Doctor	Modest irritation is the only expected effect, and	
	should have no serious consequences except	
	perhaps in the case of direct eye contact.	
	Contaminated external surfaces should be flooded	
	with water, and direct eye contact deserves eye	
	specialist check. If ingested, gastrointestinal irritation	
	but not caustic burns are to be expected; dilution with	
	water indicated as may be gastric evacuation via	
	emesis or large if large doses or severe irritation is	
	evident. Demulcents should be helpful. No systemic	
	effects are expected.	
Special Protection		
Ventilation	Use only in well ventilated area. Control dust in work	
	place at or below recommended (5 mg/m³)	
Recommended Personnel Protective Equipment		

Respiratory	When exposure above established standard is likely,		
	a respiratory protection such as dust mask be used.		
Eyes	Cup type chemical goggles and/or full face mask		
Gloves	Rubber or neoprene gloves		
Footware	Rubber or neoprene footware		
Emergency Accident			
Precautions and	Wash area with large amounts of water. Keep		
Procedure	material cool and dry		
Storage and Handling			
Storage and	Avoid contamination and wear suitable protective		
Handling	clothing. Keep material dry. Store in a clean dry		
	place. Do not store or expose to heat source such as		
	steam pipe, radiant heaters, hot are vents, or near		
	welding sparks. Avoid contact with reducing agents.		
	Reacts with moisture. If compounded with organic or		
	combustible material, be sure to exclude moisture.		
	Keep containers tightly closed when not in use.		
	Disposal, Spill or Procedures		
Procedure for	Dilute with a large volume of water. Hold in a pond or		
Release of Spill	diked area Dispose of according to method outlined		
	below for waste disposal.		
Waste Disposal	An acceptable method of disposal is to dilute with a		
Method	large amount of water and allow the discharge into a		
	suitable treatment system in accordance with all local		
	and state environmental laws, rules, regulations,		

	standards, and other requirements, because	
	acceptable method of disposal may vary by location	
	and because regulatory requirements may change.	
	The appropriate regulatory agencies should be	
	contacted prior to disposal.	
Transportation		
Precautions	Drums/bags should be stacked properly in transit,	
	make sure to avoid moisture and excessive heat	
UN Number	1457	
Type of Packages		
Type of	Polyethylene bags/ Fiber drums with polyliner	
Packages	meeting specifications according to USA DOT code	
	21C115.	